

SECTION 101100

SERIES 200

BURLAP WEAVE VINYL



SPECIFICATION

| | | | |
|---------------|---|-------------------|-----------------------|
| Style | Harborweave | Performance | |
| Fabric | Osnaburg | Tensile (Minimum) | 50 x 55 lbf |
| Weight | 21.0 oz. ply | Tear (Minimum) | 25 x 25 |
| Width | 53/54 inch | Federal Spec. | CCC-W-408A, Type II |
| Repeat | None | CFFA Spec. | CFFA-W-101-D, Type II |
| Matching Info | Random match, reverse hang | | |
| Cleaning | Normal cleaning should be done with mild ingredients such as soap detergent and water. If sustained and stronger cleaning is required, liquid household cleaners such as Lestoil should be used. Rinse with clean water and dry with absorbent cloth. Stains should be removed as quickly as possible as time is especially important for removing material containing colors or solvents such as ball point ink, nail polish, lipstick, paint... | | |
| | Fire Testing NFPA 101 Life Safety Code NFPA255 (UL723, CA S102M) Tunnel test1 Type 1 Class A Rating NFPA 286 Corner Burn Test2 Meets requirements for Flame Spread,Smoke Developed and Flashover UL Labeled and Listed | | |
| | 100% water-based inks/Cadmium Free Vinyl wall-coverings are treated with an antimicrobial to resist the growth of mildew and bacteria. | | |
| | Other fabric colors and patterns are available. Color and pattern may vary from monitor to monitor. Actual samples available upon request. Colors may vary slightly between dye lots. | | |